




FOLDABLE TOWER (optional)



PROTECTED TANK



ROBUST WINCH UNIT



4 GUYLINES



The **K 301-H** is a tractor / 3-point mounted yarder for uphill logging. It assures easy handling, reliable and rugged design, as well as very short set up and dismantling time. Particularly suitable for thinning and small wood harvesting operations.

SPECIFICATIONS

LINE CAPACITY	STANDARD	ALTERNATIVE	LINE PULL	
Skyline	1700' Ø 5/8" · 550 m Ø 16 mm swaged	1150' Ø 3/4" · 400 m Ø 18 mm swaged	Skyline	5.09 t · 50 kN
Mainline	1250' Ø 7/16" · 500 m Ø 10 mm swaged	1800' Ø 3/8" · 630 m Ø 9 mm swaged	Mainline	2.65 t · 26 kN
Guyline	4x160' Ø 5/8" / 2x33' 4x50 m Ø 16 mm / 2x10 m extensions	-		

LINE SPEED

Without payload	user defined by brake
With payload	up to 1115 ft / min · 340 m/min

POWER STATION

- Cummins QSB 4.5 diesel engine (EU-STAGE III A) with 110 PS
- Allison AT545 automatic transmission
- Cardan shaft
- Worm gear

TOWER

Standard	28' · 8.5 m
Tower extension	32' · 9.7 m
Operating range	360°

FEATURES

- Easy handling
- Proven components
- Powerful transmission for the mainline
- Large lockable storage spaces
- Hydraulic tower lift
- 180 Ah accumulators for a safe start at any temperature
- 200 liter diesel tank
- Optimal maintenance accessibility
- Cost effective
- Foldable tower 1.2 m (optional)

CARRIAGE

	SKA 1 	SKA 1-Z 
	Ø 1/2"-1" · Ø 12-24 mm	Ø 1/2"-1" · Ø 12-24 mm
	Ø 5/16"-7/16" · Ø 8-11 mm	Ø 5/16"-7/16" · Ø 8-11 mm
	approx. 350 lbs · 160 kg	approx. 420 lbs · 190 kg
	approx. 1.5 t	approx. 1.5 t

