



4 GUYLINE WINCHES



WITH FOLDABLE TOWER (optional)



NEATLY ARRANGED WINCHES



P.T.O. SHAFT



SIMPLE CONTROL





The **K 301-T** is a tractor / 3-point mounted yarder for uphill logging. It assures easy handling, reliable and rugged design, as well as very short set up and dismantling time. Particularly suitable for thinning and small wood harvesting operations.

SPECIFICATIONS

LINE CAPACITY	STANDARD	ALTERNATIVE	LINE PULL	
Skyline	1700' Ø 5/8" · 500 m Ø 16 mm swaged	1150' Ø 3/4" · 400 m Ø 18 mm swaged	Skyline	5.09 t · 50kN
Mainline	1800' Ø 3/8" · 630 m Ø 9 mm swaged	1250' Ø 7/16" · 500 m Ø 10 mm swaged	Mainline	2.65 t · 26 kN
Guyline	4x160' Ø 5/8" / 2x30' 4x50 m Ø 16 mm / 2x10 m extensions	—		

LINE SPEED

Without payload	user defined by brake
With payload	up to 605 ft/min · 185 m/min

POWER STATION

- P.T.O. driven of the tractor (mechanically driven)
- Engine power of the tractor: 66 kW (90 hp) with an auxiliary transmission
- Mainline- and skylinedrums are each driven by hydraulically operated single-disc Dry clutches coupled to the common constantly rotating winch shaft

TOWER

Standard	28' · 8.5 m
Tower extension	32' · 9.7 m
Operating range	360°

FEATURES

- 4 guylines
- Easy handling
- Great distance coverage
- Compact and cost effective solution
- With three-point mounting
- Working direction on both sides of the vehicle possible
- With CE-compliant integrated deadman circuit
- Foldable tower 1.2 m (optional)

CARRIAGE

	SKA 1	SKA 1-Z
	Ø 1/2"-1" · Ø 12-24 mm	Ø 1/2"-1" · Ø 12-24 mm
	Ø 5/16"-7/16" · Ø 8-11 mm	Ø 5/16"-7/16" · Ø 8-11 mm
	approx. 350 lbs · 160 kg	approx. 420 lbs · 190 kg
	approx. 1.5 t	approx. 1.5 t

